



A comfortable ergonomic viewing position for computer monitors is essential for preventing eye and neck strain. LiftTEC Arms move smoothly and stay in place with one-handed operation, providing easy adjustments for a perfect personal fit.

The LiftTEC Arm III is a two-part, die case aluminum monitor arm with a range of 20.28" and a maximum height of 12" above the desk surface. Designed for greater vertical movement, the Arm III allows the monitor to be positioned much lower on a desk surface. Available in two capacities, the Arm I can hold a monitor weighing up to 18 or 33 lbs. Gas-Spring Technology makes it easy to po-

sition the monitor and keep it in place. The entire arm can be rotated 360° around its table mount for easily sharing your view. It provides a clean, modern style to suit any work environment.

3-in-1 table mount options are included with the Arm I - Drilling Screw, Grommet, and System Clamp. Models are also available for TSS column mount, SlatWall mount, or a Wall Mount.

The Arm II is equipped with a Quick Release monitor mount – simply click the monitor in place and tilt to the perfect viewing angle. Cable clips are included to maintain a neat, organized appearance.

| Item Number | Base Option | Capacity | Range |
|--------------|---|----------|--------|
| 930+3089+000 | System Clamp / Grommet / Drilling Screw | 18 lbs | 20.28" |
| 930+3159+000 | System Clamp / Grommet / Drilling Screw | 33 lbs | 20.28" |
| 980+3089+000 | TSS Column Mount | 18 lbs | 21.54" |
| 980+3159+000 | TSS Column Mount | 33 lbs | 21.54" |
| 981+3089+000 | SlatWall | 18 lbs | 21.65" |
| 931+3089+000 | Wall Mount | 18 lbs | 21.65" |







FEATURES

- Adjustability: tilt/turn angle, height, rotation
- Range: 20.28" to 21.65"
- Carrying capacity: up to 18 or 33 lbs
- Maximum height of monitor mount from desk surface: 12"
- Pivot: 360 degree pivot on table mounts; 180 degrees on column, slat, and wall mounts
- Gas Spring Technology for two-fingered positioning
- Die cast aluminum construction for superior strength
- German engineered for quality
- Mounting standard: VESA 75/100

HIGHLIGHTS

| | | | | |
|---|--|--|---|--|
|  <p>VESA 75/100 STANDARD</p> |  <p>Adjustable Gas Spring</p> |  <p>Swivel 360° Up to 360°</p> |  <p>Warranty 2 Years Guarantee 2 Years</p> |  <p>Certification GS GS- Safety</p> |
|---|--|--|---|--|

BASE OPTIONS

| | | | | | |
|---|---|--|---|---|---|
|  |  |  |  |  |  |
| System Clamp | Drilling Screw | Grommet | TSS Column | SlatWall | Wall Rail |